

INVINCIBLE®

STORAGE RACKS



HUSKY
RACK & WIRE™



INVINCIBLE UPRIGHTS

UPRIGHT CAPACITIES


VERTICAL BEAM SPACING	ANSI MH 16.1 2012 UPRIGHT FRAME			
	IU18	IU24	IU29	IU35
36	21,450	29,410	39,040	46,140
42	19,880	27,490	36,280	42,770
48	18,160	25,390	33,290	39,130
54	16,350	23,170	30,170	35,360
60	14,510	20,890	27,010	31,550
66	12,690	18,600	23,870	27,800
72	10,960	16,330	20,800	24,150
78	9,540	14,280	18,100	20,950
84	8,370	12,570	15,870	18,330
90	7,390	11,140	14,010	16,160
96	6,570	9,930	12,460	14,340

- For vertical beam spacing greater than 96", please contact your distributor.
- Beam spacing (vertically) is measured from top of beam to top of beam starting from the floor to the top of the first beam and so on.
- Uprights and beams constructed of HSLA prime, U.S. made, high-strength steel. (Documented verification available on request).
- Maximum upright height available is 46'. For more information on additional upright frame configurations please contact your Regional Manager or inside sales at 704-483-1900.
- Standard baseplates are 4" x 4.25" x 0.13". Oversized baseplates available upon request.
- PE stamped drawings with calculations available for projects with permitting requirements.
- Rack Structures - Husky Rack & Wire racking can be integrated to support pushback, pallet flow, carton flow, catwalks, and mezzanine systems. Please contact our project management staff or your Regional Manager for assistance.

DEPTH	HEIGHT	3" X 1-5/8" (14 GA)	3" X 3" (14 GA)	3" X 3" (13 GA)	3" X 3" (12 GA)
36"	96"	IU18360096	IU24360096	IU29420096	IU35360096
	120"	IU18360120	IU24360120	IU29420120	IU35360120
	144"	IU18360144	IU24360144	IU29420144	IU35360144
	168"	IU18360168	IU24360168	IU29420168	IU35360168
	180"	IU18360180	IU24360180	IU29420180	IU35360180
	192"	IU18360192	IU24360192	IU29420192	IU35360192
	240"	IU18360240	IU24360240	IU29420240	IU35360240
	288"	-	IU24360288	IU29420288	IU35360288
42"	96"	IU18420096	IU24420096	IU29420096	IU35420096
	120"	IU18420120	IU24420120	IU29420120	IU35420120
	144"	IU18420144	IU24420144	IU29420144	IU35420144
	168"	IU18420168	IU24420168	IU29420168	IU35420168
	180"	IU18420180	IU24420180	IU29420180	IU35420180
	192"	IU18420192	IU24420192	IU29420192	IU35420192
	240"	IU18420240	IU24420240	IU29420240	IU35420240
	288"	-	IU24420288	IU29420288	IU35420288
48"	96"	IU18480096	IU24480096	IU29480096	IU35480096
	120"	IU18480120	IU24480120	IU29480120	IU35480120
	144"	IU18480144	IU24480144	IU29480144	IU35480144
	168"	IU18480168	IU24480168	IU29480168	IU35480168
	180"	IU18480180	IU24480180	IU29480180	IU35480180
	192"	IU18480192	IU24480192	IU29480192	IU35480192
	240"	IU18480240	IU24480240	IU29480240	IU35480240
	288"	-	IU24480288	IU29480288	IU35480288



Complies with current RMI Engineering Standards.




INVINCIBLE BEAMS



Invincible's teardrop pattern sets the industry standard and accepts most teardrop style beams. Beams feature the patented Bowlock® safety clip which installs automatically to prevent dislodgement. Many standard sizes available to ship in 48 hours.



IBX = 16 GA
IBN = 14 GA
IBH = 13 GA



CAPACITY PER PAIR

BEAM SIZE	48"	60"	72"	84"	92"	96"	108"	120"	144"	LONGER BEAM OPTION
3.0"	IBX-30048 7,580#	IBX-30060 6,300#	IBX-30072 5,240#	IBX-30084 4,010#	IBX-30092 3,430#	IBX-30096 3,190#	IBX-30108 2,610#	IBX-30120 2,190#	IBX-30144 1,610#	CALL
3.5"	IBX-35048 9,089#	IBX-35060 7,480#	IBX-35072 6,420#	IBX-35084 5,310#	IBX-35092 4,520#	IBX-35096 4,190#	IBX-35108 3,410#	IBX-35120 2,840#	IBX-35144 2,080#	CALL
3.92"	IBX-39048 10,470#	IBX-39060 8,590#	IBX-39072 7,320#	IBX-39084 6,420#	IBX-39092 5,620#	IBX-39096 5,210#	IBX-39108 4,220#	IBX-39120 3,500#	IBX-39144 2,540#	CALL
4.32"	IBX-43048 11,840#	IBX-43060 9,670#	IBX-43072 8,220#	IBX-43084 7,170#	IBX-43092 6,630#	IBX-43096 6,270#	IBX-43108 5,060#	IBX-43120 4,190#	IBX-43144 3,020#	CALL
4.85"	IBX-48048 13,970#	IBX-48060 11,360#	IBX-48072 9,610#	IBX-48084 8,370#	IBX-48092 7,710#	IBX-48096 7,430#	IBX-48108 6,510#	IBX-48120 5,360#	IBX-48144 3,840#	CALL
4.85"	IBN-48048 16,210#	IBN-48060 13,150#	IBN-48072 11,110#	IBN-48084 9,650#	IBN-48092 8,890#	IBN-48096 8,560#	IBN-48108 7,380#	IBN-48120 6,060#	IBN-48144 4,330#	CALL
5.5"	IBN-55048 19,480#	IBN-55060 15,750#	IBN-55072 13,260#	IBN-55084 11,480#	IBN-55092 10,560#	IBN-55096 10,150#	IBN-55108 9,100#	IBN-55120 8,000#	IBN-55144 5,680#	CALL
6.0"	IBN-60048 22,200#	IBN-60060 17,910#	IBN-60072 15,050#	IBN-60084 13,010#	IBN-60092 11,940#	IBN-60096 11,480#	IBN-60108 10,280#	IBN-60120 9,330#	IBN-60144 6,910#	CALL
6.0"	IBH-60048 27,470#	IBH-60060 22,140#	IBH-60072 18,580#	IBH-60084 16,040#	IBH-60092 14,710#	IBH-60096 14,130#	IBH-60108 12,650#	IBH-60120 11,460#	IBH-60144 8,300#	CALL

INVINCIBLE ACCESSORIES/OPTIONS

FLOOR MOUNT POST PROTECTOR



Size
12" x 1/4"
18" x 1/4"
24" x 1/4"

Catalog Number
I5712-P
I5718-P
I5724-P

BOLT ON POST PROTECTOR



Size
12" x 1/4"
18" x 1/4"
24" x 1/4"

Catalog Number
I5812
I5718
I5724

ROW SPACER



Distance between upright frames (back to back)

Catalog Number

6"	RSIN06
8"	RSIN08
12"	RSIN12
18"	RSIN18

Furnished with necessary bolts & nuts.
Connects and rigidly holds racks at set spacing.
Recommended when upright height is more than six times depth.

WATERFALL CROSSBAR



Upright frame depth

Catalog Number

36"	A1036G
42"	A1042G
48"	A1048G

RACK GUARD













AISLE SHIELD



WIRE DECK



Color Options

Standard Colors			Optional Colors								
	PH01 Green	PH05 Orange		PH03 Beige	PH04 White	PH06 Blue	PH08 Red	PH11 Vista Green	PH71 Safety Yellow	PH02 Gray	PH10 Yellow

High quality polyurethane paint. Environmentally safe, does not contain lead.
Standard colors: green uprights & orange beams (other colors available upon request see chart above).
Colors outside of the listed above are available, please contact inside sales for details.

Husky Rack and Wire makes continuous improvements in all its products. We reserve the right to change specifications without notice.

Warranty Information

For warranty information applicable to all our products, refer to the Husky Rack and Wire Terms and Conditions of Sale, which are accessible at www.huskyrackandwire.com/terms_and_conditions.html



IMP 22346



BodeEquipment.com
(800)797-5699



Item #80146-6